

# MORBARK® BEEVER™ M8D




## BENEFITS

- Perfect for rental yards, landscapers, golf courses and pruning crews, this high-capacity unit is easy to transport and operate.
- The only chipper in its class to combine both a wide infeed chute opening and 1 ¼" thick chipping disc, the M8D has a 251-pound disc and shaft weight provides more inertia to power through material and continuously feed material.
- With a single top feed wheel compression system and 32.3 ci hydraulic motor with spring-assisted down pressure, the M8D generates more than 2,300 lb/ft of material pulling force and approximately 1,000 lb/ft of combined down pressure to easily feed a variety of materials.
- Like all Morbark equipment, the M8D is a long-lasting, durable machine backed by a world-class parts and service support team.



### Belt Drive

Direct drive with belt power transfer eliminates clutch components and over center belt tensioning systems, reducing problem areas and easing maintenance burdens.



### Infeed Chute

Infeed chute with 96-cubic-inch throat opening allows for easy material feeding and reduced trim labor and folds to reduce transport and storage length.



### 360° Swivel Discharge

360° swivel discharge with adjustable chip deflector puts chips right where they're needed without removing the Beever from the tow vehicle.



### Feed System

A top feed wheel compression system with spring-assisted down pressure easily breaks down a variety of materials.

## SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 5/14/12

### General

Chipping capacity . . . . . 8"  
 Height . . . . . 7'4"  
 Width . . . . . 5'3"  
 Length (transport) . . . . . 12'3 ½"  
 Length (operating) . . . . . 14'3"  
 Gross weight . . . . . 2,150–2,750 lbs.  
 Suspension . . . . . 2,000 lb. torsion  
 Infeed opening . . . . . 33 ½" wide x 24 ¼" high  
 Throat opening . . . . . 12" wide x 8" high  
 Feed wheel . . . . . 11 ½" wide x 9" diameter  
 Disc dimensions . . . . . 1 ¼" thick x 28" diameter  
 Engine . . . . . Kohler or Kubota  
 Horsepower . . . . . 35–44 HP  
 Fuel capacity . . . . . 10 gallons  
 Hydraulic capacity . . . . . 10 gallons  
 Frame . . . . . 2" x 4" Tubular  
 Tires . . . . . (2) 185/80R14"  
 Hitch . . . . . 2" Ball

### Equipment Highlights

Direct drive with belt power transfer  
 Automatic feed system  
 Chipper disc with two 10 ½" x 4" x ¾"  
 dual-edged chipper knives and four full-length,  
 bolt-on, chip throwing paddles  
 Reversible feed works control bar and dual safety  
 cables located within infeed chute  
 Pinned chipper hood access with integrated hood  
 safety device to disconnect the start system when  
 the chipper hood is opened and allow ease of  
 disc maintenance.  
 3" x 4" tubular steel fixed length drawbar and  
 ¾" thick safety chains with clasp hooks  
 Morthane Paint System: A chemically cured,  
 electrostatically applied urethane coating with  
 high-gloss finish, built-in UV protection, chip and  
 chemical resistance and corrosion protection

### Additional Features

Fuel tank sight gauge, drain plug and  
 shut-off valve  
 Hydraulic tank shut-off valve, drain plug,  
 clean-out cover and vented filter head assembly  
 with dipstick to check oil level  
 8D, 1400 CCA Battery  
**Options**  
 Variable speed flow control  
 2,500 lb. Torflex suspension axle with electric  
 brake system, electric brake actuator and 185R14  
 tires with rims  
 Custom paint and logo packages  
 2 ½" lunet ring  
 Knife saver tool  
 Engine stop on infeed  
 Material pushing tool  
 Spanish and English safety decals



**MORBARK®**  
 BUILDING EQUIPMENT THAT CREATES OPPORTUNITIES

*Authorized Morbark Dealer*

**ALEXANDER**  
**EQUIPMENT COMPANY INC.**

4728 Yender Avenue ■ Lisle, IL 60532  
 (630)663-1400 ■ [www.alexequip.com](http://www.alexequip.com)